

ID select control method is mentioned last page.

<Write>

Operation		Com	Parameter	
Power ON	---	PON	---	---
Power OFF	---	POF	---	---
Dual picture mode	OFF/P and P/P out P/P in P	DWA	***	OFF/TWN/POP/PIP
Main picture Input Select	Toggle/Slot1/Slot2/Slot3/PC (37"Slot3:Nil)	IMS	***	(NONE)/SL1/SL2/SL3/PC1
Sub picture Input Select	Toggle/Slot1/Slot2/Slot3/PC (37"Slot3:Nil)	ISS	***	(NONE)/SL1/SL2/SL3/PC1
Aspect	Zoom/Full/Just/Normal/ Panasonic Auto Setting/(Toggle)	DAM	****	ZOOM/FULL/JUST/NORM/ SELF/(NONE)
Picture Mute	ON/OFF/(Toggle)	VMT	*	1/0/(NONE)
Audio Mute	ON/OFF/(Toggle)	AMT	*	1/0/(NONE)
Audio Volume	0 – 63	AVL	**	00-63
Volume Up	---	AUU	---	---
Volume Down	---	AUD	---	---
Picture Menu	Standard/Dynamic/Cinema/Auto	VPC	MEN***	STD/DYN/CNMAUT
Picture	-30 - 30	VPC	PIC***	-30 – 000 - +30(030)
TINT	-30 - 30	VPC	TIN***	-30 – 000 - +30(030)
Color	-30 - 30	VPC	COL***	-30 – 000 - +30(030)
Brightness	-30 - 30	VPC	BLK***	-30 – 000 - +30(030)
Color Temperature	Warm/Normal/Cool	VPC	TMP***	WRM/MID/COL
Sharpness	-15 - +15	VPC	SHP***	-15 – 000 - +15(015)
Technical	ON/OFF	VWB	TEC*	1/0
Black Extension	0 – 8	VWB	BEX***	+00(000) - +08(008)
W/B High R	-30 – 30	VWB	RDR***	-30 – 000 - +30(030)
W/B High B	-30 – 30	VWB	BDR***	-30 – 000 - +30(030)
W/B Low R	-30 – 30	VWB	RCT***	-30 – 000 - +30(030)
W/R Low B	-30 – 30	VWB	BCT***	-30 – 000 - +30(030)
Gamma	2.0/2.2/2.5	VWB	GMM**	20/22/25
Audio Menu	Auto/Standard	AAC	MEN***	AUT/STD
Bass	-15 – 15	AAC	BAS***	-15 – 000 - +15(015)
Treble	-15 – 15	AAC	TRE***	-15 – 000 - +15(015)
Balance	-30 – 30	AAC	BAL***	-30 – 000 - +30(030)
SYNC Signal setting	H&V/On-GREEN/On-VIDEO	SSG	SNC***	HAV/GRN/VID
Color System	NTSC/PAL/SECAM/M.NTSC/ AUTO	SSG	COS***	NTS/PAL/SCM/MNT/AUT
Vertical Position	-124+124	DGE	VPO****	-124 – 0000 - +124(0124)
Vertical Size	-62+62	DGE	VSZ****	-062 – 0000 - +062(0062)
Horizontal Position	-124+124	DGE	HPO****	-124 – 0000 - +124(0124)
Horizontal Size	-124+124	DGE	HSZ****	-124 – 0000 - +124(0124)

Operation		Com	Parameter	
Clock Phase	-16+16	DGE	CLK****	-016 – 0000 - +016(0016)
Multi Screen Setting	ON/OFF, 2x2/3x3, Screen No.(2x2 : 01-04, 3x3 : 01-09)	MDC	****	1/0,0/1,01-09
Screensaver (Function Select)	White Scroll Bar/Image Reversal	SSC	FNC*	0/1
Screensaver (Mode Selection)	OFF/Interval/ Time Designation/ON	SSC	MOD*	0/1/2/3
Screensaver (Interval)	00:00 – 23:59 (Periodic), 00:00 – 23:59 (Operating time)	SSC	INT*****	0000-2359, 0000-2359
Screensaver (Time of Day)	00:00 - 23:59 (Start Time), 00:00 - 23:59 (Finish Time)	SSC	TIM*****	0000-2359, 0000-2359
Screensaver (Side Panel Adjustment)	OFF/Low/Mid/High	SSC	SPC*	0/1/2/3
Set up Timer1 (Present Time of Day)	0 (Fix), 00:00-23:59 (Input Present Time by hand once)	TIM	NOW*****	0, 0000-2359
Set up Timer2 (Power ON Time)	Enable/cancel, 00:00-23:59	TIM	PON*****	1/0, 0000-2359
Set up Timer3 (Power OFF Time)	Enable/cancel, 00:00-23:59	TIM	POF*****	1/0, 0000-2359

<Read>

Operation	COM	Parameter		Call Back	Status
Power ON	QPW	---	*	1/0	ON/OFF
Dual Picture mode	QDW	---	***	OFF/TWN/POP/PIP	Off/P and P/P out P/P in P
Main picture Input Select	QMI	---	***	SL1/SL2/SL3/PC1	Slot1/Slot2/Slot3/PC
Sub picture Input Select	QSI	---	***	SL1/SL2/SL3/PC1	Slot1/Slot2/Slot3/PC
Aspect	QAS	---	****	ZOOM/FULL/JUST/NORM/ SELF	Zoom/Full/Just/Normal /Panasonic Auto Setting
Picture Mute	QVM	---	*	1/0	ON/OFF
Audio Mute	QAM	---	*	1/0	ON/OFF
Volume	QAV	---	**	00-63	0 - 63
Picture Menu	QPC	MEN	MEN***	STD/DYN/CNM/AUT	Standard/Dynamic/ Cinema/Auto
Picture	QPC	PIC	PIC***	-30 - 000 - +30	-30 - 30
TINT	QPC	TIN	TIN***	-30 - 000 - +30	-30 - 30
Color	QPC	COL	COL***	-30 - 000 - +30	-30 - 30
Brightness	QPC	BLK	BLK***	-30 - 000 - +30	-30 - 30
Color Temperature	QPC	TMP	TMP***	WRM/MID/COL	Warm /Normal/ Cool
Sharpness	QPC	SHP	SHP***	-15 - 000 - +15	-15 - 15
Black Extension	QWB	BEX	BEX***	+00-+08	0 - 8
Technical	QWB	TEC	TEC*	1/0	ON/OFF
W/B High R	QWB	RDR	RDR***	-30 - 000 - +30	-30 - 30
W/B High B	QWB	BDR	BDR***	-30 - 000 - +30	-30 - 30
W/B Low R	QWB	RCT	RCT***	-30 - 000 - +30	-30 - 30
W/B Low B	QWB	BCT	BCT***	-30 - 000 - +30	-30 - 30
Gamma	QWB	GMM	GMM**	20/22/25/SC	2.0/2.2/2.5/S-Curve
Audio Menu	QAC	MEN	MEN***	AUT/STD	Auto/Standard
Bass	QAC	BAS	BAS***	-15 - 000 - +15	-15 - 15
Treble	QAC	TRE	TRE***	-15 - 000 - +15	-15 - 15
Balance	QAC	BAL	BAL***	-30 - 000 - +30	-30 - 30
SYNC Signal setting	QSG	SNC	SNC***	HAV/GRN/VID	H&V/On-GREEN/On-VIDEO
Color System	QSG	COS	COS***	NTS/PAL/SCM/MNT/AUT	NTSC/PAL/SECAM/M.NTSC/AUTO
Vertical Position	QGE	VPO	VPO****	-124 - 0000 - +124	-124 - +124
Vertical Size	QGE	VSZ	VSZ****	-062 - 0000 - +062	-62 - +62
Horizontal Position	QGE	HPO	HPO****	-124 - 0000 - +124	-124 - +124
Horizontal Size	QGE	HSZ	HSZ****	-124 - 0000 - +124	-124 - +124
Multi Screen Setting	QDC		****	0/1, 0/1, 01-09	OFF/ON, 2x2/3x3, Screen No(2x2 : 01-04, 3x3 : 01-09)
Screensaver (Function Select)	QSC	FNC	FNC*	0/1	White Bar Scroll / Negative
Screensaver (Mode Selection)	QSC	MOD	MOD*	0/1/2/3	OFF/Interval/ Time Designation/ON
Screensaver (Interval)	QSC	INT	INT*****	0000-2359,0000-2359	00:00 - 23:59 (Periodic Time), 00:00 - 23:59 (Operating Time)

